

Daker DK Plus 10000 – Inverter 3-1

3 101 78



TABLE OF CONTENTS Page

| | |
|-----------------------------|---|
| 1. General features..... | 1 |
| 2. Technical features | 1 |

1. GENERAL FEATURES

The Legrand UPS Daker DK Plus 10000 model is an uninterruptible power source with high frequency PWM technology, Double Conversion On-Line, solid neutral, Rated Power 10,000 VA – 9000 W. It does not contain internal batteries but can be connected to one or more external cabinets containing valve-regulated, hermetically sealed accumulator batteries. The fact that it does not contain internal batteries reduces the dimensions of this UPS to just three rack units.

The architecture of this UPS means it can be installed in either a Tower configuration or inside Rack cabinets.

The rectifier of the UPS is comprised of a control and regulating circuit (PFC), which, in addition to normal rectifier functions also:

- automatically corrects the power factor of the load to restore it to a value of >0.99 with a load applied at the output at 20% of the rated load;
- power the inverter without requiring energy from the batteries, even when there is very low voltage from the mains;
- ensures a total harmonic distortion of the input current THD_{in} < 3% without the addition of filters or supplementary parts.

The bypass circuit is designed and built in compliance with the following:

- Electromechanical switch
- Command and control logic managed by a microprocessor that:
- automatically transfers the load directly onto the primary mains line without interrupting the power supply if any conditions of overload, over temperature, continuous voltage outside of the tolerances and inverter anomaly arise;
- automatically re-transfers the primary mains line load to an inverter line, without interrupting the power supply, once normal conditions of the load have been restored;
- if the primary mains line and the inverter are not synchronized, the bypass must be disabled.

A diagnostic and shutdown software (UPS Communicator), if accordingly installed in a PC connected to the UPS, allows you to access all of the operational data, make adjustments and settings to the special functions and control Windows and Linux operating system shutdown.

An optional software (UPS management software) offers hierarchic multiserver shutdown and remote management of the UPS for any operating system in a heterogeneous network (Windows, Novell, Linux and the common Unix).

Daker DK 10000 Plus is managed by a microprocessor and is able to display, on a control panel and LCD screen, the alarms and operating modes described below:

- normal operation
- output frequency that is not synchronized with the input
- battery-powered operation
- operation in bypass mode
- faulty power module
- overloaded
- generic anomaly
- incorrect neutral connection

The Daker DK Plus 10000 Static Uninterruptible Power Supply bears the CE marking, pursuant to Directives 2014/35, 2104/30, and is designed and built in compliance with the following standards:

- EN 62040-1 “General and safety requirements for UPSs used in areas that are accessible to the operator”
- EN 62040-2 “Electromagnetic Compatibility requirements (EMC)”
- EN 62040-3 “Performance and test method requirements”

2. TECHNICAL FEATURES

| General Features | |
|---------------------|--------------------------------------|
| Nominal power (VA) | 10000 |
| Active power (W) | 9000 |
| Technology | On-Line Double Conversion VFI-SS-111 |
| Waveform | Sinusoidal |
| UPS architecture | convertible tower and rack 19 |
| Surge Rating | 1900 |
| ECO Mode efficiency | %97,5 |

| Input | |
|---------------------|----------------------------|
| Input voltage | 380V 3F+N |
| Input frequency | 50-60 Hz ±5% Autosensing |
| Input Voltage Range | 305 V - 485 V at full load |
| Input power factor | > 0.99 |

| Output | |
|----------------------------|---|
| Output voltage | 230V ± 1% |
| Output frequency (nominal) | 50/60 Hz (can be set from the LCD panel) +/- 0.1% |
| Crest Factor | 1:3 |
| THD Output voltage | Linear load 2% Nonlinear load 5% |
| Output Voltage Tolerance | ±1% |

2. TECHNICAL FEATURES *(continued)*

| Batteries | |
|-----------------------------|-----|
| Uptime Expansion | yes |
| Number of batteries | - |
| Battery series Type/Voltage | - |
| Uptime with 80% load (min) | - |

| Communication and management | |
|------------------------------|--|
| Display and Signals | Four buttons and four LEDs to monitor the status of the UPS in real time |
| Communication Ports | RS232 serial ports, USB |
| Remote Management | available |
| Network interface slot | SNMP |

| Mechanical features | |
|---|---------------------|
| Measurements H x L x D (mm) | 440 x132 (3U) x 680 |
| Battery Cabinet Measurements H x L x D (mm) | 440 x132 (3U) x 680 |
| Net Weight (kg) | 26 |

| Environmental conditions | |
|----------------------------|----------------------|
| Operating temperature (°C) | 0 ÷ 40 °C |
| Degree of protection | IP20 |
| Relative humidity (%) | 0-95% non-condensing |
| Noise level at 1 m (dBA) | < 50 |
| Heat Loss (BTU/h) | 1636 |

| Certifications | |
|----------------|------------------------------------|
| Standards | EN 62040-1, EN 62040-2, EN 62040-3 |